



## **SQUIR**

**ACCESS ROPES C€** EN1891-A

**DIAMETER** 

Ø 11.5 mm

**COLOUR OPTIONS** 

RED

YELLOW

**LENGTH OPTIONS** 

Red: 60, 70, 200 & 900 meters

Yellow: 60, 70, 200 & 900 meters (Other lengths available on request)

**TERMINATION** 

None available

**TECHNICAL SPECIFICATIONS** 

 Materials / construction: 32-strand Polyester sheath with X-Braid Polyamide core

Designed for SRT or use as an access line, the redeveloped Squir has a more durable but very flexible polyester sheath. It's low stretch ensures that the bounce effect is kept to a minimum when climbing. Users admire the performance of the rope when combined with the

latest metal friction devices on the market.

Static resistance: 30kN

• Resistance with figure of 8 knot: 21kN

• Mass per meter: 91gram • Sheath percentage: 43% • Sheath slippage: 0.2% • Elongation 50/150Kg: 2%

• Knotability: 0.74

Retraction with water: 1.5%

Reference: MJ100+++++

## **KEY FEATURES**

- Very low stretch
- Superior wear resistance
- Heat treated for extra stability
- Exciting colour combinations
- Retains it's flexibility over time





mycourant.com



**Courant Vertical Living** 



courant\_vertical\_living